



Husqvarna S 26

S 26 is a powerful single-phase HEPA dust extractor to match the grinding machines Husqvarna PG 280, PG 450 and early entry saw Soff-Cut 150. It also matches small scarifiers and shot blasters as well as handheld power tools. This professional dust extractor is suitable for building, grinding, plaster and concrete dust. Equipped with two tested and certified HEPA H13 filters. Features include Jet Pulse pre-filter cleaning, hour counter and vacuum meter for filter control. The non-marking wheels are puncture free and lock at the front. The Longopac® bag hose system ensures simple, dust-free bag changes.



Durable design

Corrosion-resistant steel clamps, welded frame with dust bag platform and durable steel handle make it ready to serve for many years.



Easy and efficient filter cleaning

The Jet Pulse filter cleaning system ensures high continuous airflow thanks to easy and efficient cleaning of the conical main filter without opening the machine.

Efficient filtration system

The three separate filtering stages result in longer working time between filter cleaning. The dust is filtered through a cyclone chamber, which separates the heaviest parts, up to 95% of the dust, before the washable main filter. The HEPA micro filters are individual tested and certified to capture 99.99% of the remaining silica dust in the respirable fraction (0.3µm).



Easy to transport

The welded frame enables easy transportation by resting the machine on the frame.





ALQUILER Y VENTA DE MAQUINARIA

- Efficient filtration system
- Easy and efficient filter cleaning
- Durable design
- Easy to transport
- High Efficiency Particulate Air filter

FEATURES

- Easy-to-read airflow monitoring
- Clean and simple bag change
- For demanding industrial applications
- Control

Technical Specifications	
MOTOR	
Fases	1~
Voltaje	230 V
Corriente nominal, A	10.4 A
Vacio máx.	220 mbar
Diámetro máximo de brocas, manual	2.4 kW
Máx. profundidad de corte	1275 mm
Máx. profundidad de corte	756 mm
Máx. profundidad de corte	546 mm
Peso	47 kg
ESPECIFICACIONES	
Air Flow	400 m³/h
HEPA filters 99.99% at 0.3 microns	2
Vacio máx.	220 mbar
Water lift	90 pulg
EMBALAJE	
Packaging length	740 mm
Packaging width	560 mm
Packaging height	1350 mm
Packaging volume	559.4 dm³